



Strojirenský zkušební ústav, s.p., Brno, Česká republika
Engineering Test Institute, Public Enterprise, Brno, Czech Republic

CERTIFICATE

Number: **E-30-20443-12**

Producer: YU CHI TAIWAN ENTERPRISE CO., LTD.
No. 2, Lane 625, Ming-Yeou Rd., Lu-Chu Dist.
Kaohsiung City, 821, Taiwan

Product,
Type/Model/Specification: Stainless steel screw
- ø 5.0 mm
- flat head, partly threaded, with sharp point, Phillips or Torx recess,
type 17
- material: stainless steel AISI 316, finish treatment: passivated
- length: (50 to 200) mm

Product identification and
findings of the initial-type
testing of the product: see Annex 1 (page 2)


Base of certificate issuance: Final Report on Initial Type-Testing of the product
30-9775/4 of 2012-11-21

Harmonized standard: EN 14592:2008, Tab. ZA.1

Strojirenský zkušební ústav, s.p., Engineering Test Institute, Public Enterprise, confirms that performed the initial-type testing of the said product according to the requirement stated in Directive 89/106/EEC, Annex III, (2) (ii), second possibility (corresponds with Government Order 190/2002 Coll. § 5 art. 1 let. b). Final Report containing initial type-testing findings and data on product identification.

Brno, 2012-11-22




.....
Ing. Pavel Štícha
Director for Certification

Certificate No. E-30-20443-12.docx; Page 1 / Total pages 2

Strojirenský zkušební ústav, s. p., Hudcova 56b, 621 00 Brno, Česká republika
Engineering Test Institute, public enterprise, Hudcova 56b, 621 00 Brno, Czech Republic

www.szutest.cz



Certificate E-30-20443-12, Annex 1

Product identification and findings of the initial-type testing of the product:

Product	characteristic yield moment $M_{y,k}$ [Nmm]		characteristic withdrawal parameter $f_{ax,k}$ [N/mm ²]		characteristic head pull-through parameter $f_{head,k}$ [N/mm ²]	characteristic tensile capacity $f_{tens,k}$ [kN]	characteristic torsional ratio
	thread part	smooth part	loading across the fibre	loading along the fibre	-	-	-
screw ø 5.0 mm	4 566	3 386	17,44	7,64	21,35	4,60	2,12
Characteristic density of wood ρ_k [kg/m ³]	-		360		360	-	450
Durability (corrosion protection)	stainless steel AISI 316 (Service Class 3 acc. to EN 1995-1-1)						

Intended use: in load bearing structural timber products.

